Worthington

SAFETY DATA SHEET

1. Identification

Product identifier Worthington Antimonial Lead Solder

Other means of identification

SDS number WC031

Recommended use Bearing repair and soldering.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer/Supplier Worthington Cylinder Corporation

Address 200 Old Wilson Bridge Road

Columbus, OH 43085

United States

Email: cylinders@worthingtonindustries.com

Telephone Number: 866-928-2657

CHEMTREC - 24 HOURS:

Within US and Canada 800-424-9300

Outside US and Canada +1 703-741-5970 (collect calls accepted)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Acute toxicity, inhalation Category 4
Germ cell mutagenicity Category 2
Carcinogenicity Category 2
Reproductive toxicity Category 1A

Specific target organ toxicity, repeated Category 1 (blood, kidney, nervous system)

exposure

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Harmful if swallowed. Harmful if inhaled. Suspected of causing genetic defects. Suspected of

causing cancer. May damage fertility or the unborn child. Causes damage to organs (blood,

kidney, nervous system) through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust/fume. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective

gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention. If swallowed: Call a poison center/doctor if

you feel unwell. Rinse mouth. If inhaled: Remove person to fresh air and keep comfortable for

breathing.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Worthington Antimonial Lead Solder

SDS US

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Lead	7439-92-1	65-99
Antimony	7440-36-0	1-35

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Immediately remove from further exposure. Get immediate medical assistance. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. Give supplemental oxygen, if available. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

Skin contact

Remove contaminated clothes and rinse skin thoroughly with water for at least 15 minutes. If skin rash or an allergic skin reaction develops, get medical attention.

Eye contact

Rinse immediately with plenty of water for at least 15 minutes. Remove any contact lenses. Get

medical attention if irritation develops or persists.

Ingestion

Immediately rinse mouth and drink a cupful of water. Never give anything by mouth to a victim who is unconscious or is having convulsions. Only induce vomiting at the instruction of medical personnel. Get medical attention immediately.

Most important

symptoms/effects, acute and delayed

Dust and fumes may irritate eyes, skin and upper respiratory tract. Contact with molten material

may cause thermal burns.

Indication of immediate medical attention and special treatment needed

Treat symptomatically. Exposure may aggravate pre-existing lungs, diseases of the blood and blood forming organs, kidneys, nervous, and possibly reproductive systems. Symptoms may be delayed.

General information

Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Extinguish with foam, carbon dioxide or dry powder.

Do not use water or halogenated extinguishing media.

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters Fire or high temperatures create: Metal oxides.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do it without risk.

General fire hazards

Solid metal is not flammable; however, finely divided metallic dust or powder may form an explosive mixture with air.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Avoid inhalation of dust from the spilled material. Wear protective clothing as described in Section 8 of this SDS. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and materials for containment and cleaning up For a dry material spill, use a HEPA (high efficiency particle air) vacuum to collect material and place in a sealable container for disposal. Avoid dust formation. Recover and recycle, if practical. Keep out of water supplies and sewers.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water. If release occurs in the U.S. and is reportable under CERCLA Section 103, notify the National

Response Center at (800)424-8802 (USA) or (202)426-2675 (USA).

SDS US

7. Handling and storage

Precautions for safe handling

Wear appropriate personal protective equipment (See Section 8). Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Avoid inhalation of dust and fumes. Avoid contact with skin and eyes. Do not get this material on clothing. Do not eat, drink or smoke when using the product. Wash thoroughly after handling. Avoid release to the environment. Follow special national provisions related to work with lead and its compounds. Pregnant women should not work with the product, if there is the least risk of lead exposure.

Any surface that comes in contact with molten metal must be preheated or specially coated and rust free. Inadvertent contaminants to product such as moisture, ice, snow, grease, or oil can cause an explosion when charged to a molten metal bath or metal furnace (preheating metal will remove moisture from product).

Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Store in a closed container away from incompatible materials. Keep out of reach of children. Keep away from food, drink and animal feedingstuffs.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Туре	Value	
Lead (CAS 7439-92-1)	TWA	0.05 mg/m3	
US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910.	1000)	
Components	Туре	Value	
Antimony (CAS 7440-36-0)	PEL	0.5 mg/m3	
US. ACGIH Threshold Limit Value	S		
Components	Туре	Value	
Antimony (CAS 7440-36-0)	TWA	0.5 mg/m3	
Lead (CAS 7439-92-1)	TWA	0.05 mg/m3	
US. NIOSH: Pocket Guide to Chen	nical Hazards		
Components	Туре	Value	
Antimony (CAS 7440-36-0)	TWA	0.5 mg/m3	
Lead (CAS 7439-92-1)	TWA	0.05 mg/m3	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Lead (CAS 7439-92-1)	300 µg/l	Lead	Blood	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

No exposure standards allocated.

Appropriate engineering

controls

Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of dust. Keep melting/soldering temperatures as low as possible to minimize the generation of fume. Shower, hand and eye washing facilities near the workplace are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Wear a face shield when working with molten

material.

Skin protection

Hand protection Wear protective gloves (i.e. latex, nitrile, neoprene).

Other Chemical resistant clothing is recommended. Heat resistant/insulated gloves and clothing are

recommended when working with molten material.

Respiratory protection

Use a respirator when local exhaust or ventilation is not adequate to keep exposures below the OEL. In a confined space a supplied respirator may be required. Selection and use of respiratory protective equipment should be in accordance with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4. Use a NIOSH/MSHA approved respirator if

Worthington Antimonial Lead Solder 913388 Version #: 01 Revision date: -Issue date: 30-June-2015

Heat resistant/insulated gloves and clothing are recommended when working with molten material. Thermal hazards

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance Silver to silver-gray metallic metal.

Solid. Physical state

Wire, ingot, pig, pipe anodes, cast or extruded bar, sheet, brick, rod, strip, tubing, ribbon, tape, **Form**

flake, and miscellaneous extruded lines, #4 Babbitt.

Silver to gray. Color Odor Odorless. **Odor threshold** Not available. Not applicable. pН

Melting point/freezing point 622.4 °F (328 °C) (Lead) / 1166 °F (630 °C) (Antimony)

Initial boiling point and boiling

range

2516 °F (1380 °C) (Antimony) 3171.2 °F (1744 °C) (Lead)

Flash point Not applicable. **Evaporation rate** Not available. Flammability (solid, gas) Non flammable.

Upper/lower flammability or explosive limits Flammability limit - lower

(%)

Not applicable.

Flammability limit - upper

Not applicable.

Not applicable. Vapor pressure Not applicable. Vapor density 9.71 - 11.29 Relative density

Solubility(ies)

Solubility (water) Not soluble in water.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not applicable **Decomposition temperature** Not available. **Viscosity** Not applicable.

10. Stability and reactivity

The product is non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Contact with incompatible materials. Avoid molten metal contact with water.

Incompatible materials Strong oxidizing agents. Reducing agents. Hydrogen peroxide (H2O2). Active metals. Strong

acids. Strong bases. Nascent hydrogen. Chlorine. Fluorine. Bromine.

Hazardous decomposition

products

Toxic metal oxides are emitted when heated above the melting point.

Under reducing condition, such as any strong acid or base plus an active metal, or in the presence

of nascent hydrogen, highly toxic stibine gas (TLV = 0.10 ppm) may be evolved.

11. Toxicological information

Information on likely routes of exposure

Harmful if inhaled. Elevated temperatures or mechanical action may form dust and fumes which Inhalation

may be irritating to the mucous membranes and respiratory tract.

Skin contact Dust may irritate skin.

Worthington Antimonial Lead Solder

Eye contact Elevated temperatures or mechanical action may form dust and fumes which may be irritating to

the eve.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the eye, mucous membranes and respiratory tract. Contact with molten material may cause

thermal burns.

Information on toxicological effects

Acute toxicity Harmful if inhaled or swallowed. Exposure to antimony and its compounds can cause

gastrointestinal pain, cough, loss of appetite, itching, skin eruptions, and irritation of skin, eyes,

nose and throat. Overexposure to Lead may lead to central nervous system disorders, characterized by drowsiness, seizures, coma and death. It should be recognized that exposures

of this magnitude in an industrial setting are extremely unlikely.

Skin corrosion/irritation Dust may irritate skin.

Serious eye damage/eye irritation

Elevated temperatures or mechanical action may form dust and fumes which may be irritating to

the eye.

Respiratory or skin sensitization

Respiratory sensitizationNo sensitizing effects known. **Skin sensitization**No sensitizing effects known.

Germ cell mutagenicity Suspected of causing genetic defects.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Lead (CAS 7439-92-1) 2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Lead (CAS 7439-92-1) Reasonably Anticipated to be a Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity May damage fertility or the unborn child. Lead is a teratogen. Elevated lead exposure of either

parent before pregnancy may increase the changes of miscarriage or birth defects. Continuous exposure may result in decreased fertility. Exposure of the mother during pregnancy may cause

birth defects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Causes damage to organs (blood, kidney, nervous system) through prolonged or repeated

exposure.

Aspiration hazard Not

Chronic effects

Not relevant, due to the form of the product.

Exposure to antimony and its compounds can cause headache, sleeplessness, dizziness, metallic taste, ulcers, weight loss, nausea, vomiting, diarrhea, impairment of sense of smell, and pain or tightness in chest. Overexposure to Lead can lead to systemic lead poisoning with symptoms of metallic taste, anemia, insomnia, weakness, constipation, abdominal pain, gastrointestinal disorders, joint and muscle pains, and muscular weakness, and may cause damage to the blood forming, nervous, kidneys and reproductive systems. Damage may include reduced fertility in both

men and women, damage to the fetus of the exposed pregnant woman, anemia, muscular weakness and kidney dysfunction.

Further information Lead is accumulated in the body and may cause damage to the brain and nervous system after

prolonged exposure.

12. Ecological information

Ecotoxicity Alloys in massive forms present a limited hazard for the environment.

Persistence and degradability The product is not biodegradable.

Bioaccumulative potential No data available.

Mobility in soil Alloys in massive forms are not mobile in the environment.

Other adverse effects None expected.

13. Disposal considerations

Disposal instructions Dispose in accordance with all applicable regulations.

Hazardous waste code Product contains lead a hazardous waste constituent regulated under 40 CFR 261.24.

Worthington Antimonial Lead Solder
913388 Version #: 01 Revision date: - Issue date: 30-June-2015

Waste from residues / unused

products

Dispose of in accordance with local regulations. Scrapped material should be sent for refining to recover precious metal content. Solid metal and alloys in the form of particles may be reactive. Its hazardous characteristics, including fire and explosion, should be determined prior to disposal.

Contaminated packaging Sine

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

US Clean Water Act Notice: The use of this solder in making joints or fittings in any private or

public drinking water supply system is prohibited by the Clean Water Act.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Lead (CAS 7439-92-1) Reproductive toxicity

Central nervous system

Kidney Blood Acute toxicity

CERCLA Hazardous Substance List (40 CFR 302.4)

Antimony (CAS 7440-36-0) LISTED Lead (CAS 7439-92-1) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Lead	7439-92-1	65-99
Antimony	7440-36-0	1-35

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Antimony (CAS 7440-36-0) Lead (CAS 7439-92-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer and

birth defects or other reproductive harm.

Worthington Antimonial Lead Solder

SDS US

913388 Version #: 01 Revision date: - Issue date: 30-June-2015

US. Massachusetts RTK - Substance List

Antimony (CAS 7440-36-0) Lead (CAS 7439-92-1)

US. New Jersey Worker and Community Right-to-Know Act

Antimony (CAS 7440-36-0) Lead (CAS 7439-92-1)

US. Pennsylvania Worker and Community Right-to-Know Law

Antimony (CAS 7440-36-0) Lead (CAS 7439-92-1)

US. Rhode Island RTK

Antimony (CAS 7440-36-0) Lead (CAS 7439-92-1)

US. California Proposition 65

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Lead (CAS 7439-92-1)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 30-June-2015

Revision date - Version # 01

United States & Puerto Rico

Further information HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings Health: 2*

Flammability: 0 Physical hazard: 0

NFPA ratings



References ACGIH

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

913388 Version #: 01 Revision date: - Issue date: 30-June-2015

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

All information in this Material Safety Data Sheet is believed to be accurate and reliable. However, no guarantee or warranty of any kind is made with regard to the accuracy of information or the suitability of the recommendations contained herein. It is the user's responsibility to assess the safety and toxicity of this product under their own conditions of use and to comply with all applicable laws and regulations.