



## REFRIGERANT

## DOT 39 NON-REFILLABLE



### SPECIFICATIONS

#### STANDARD

MODEL	7.5 INCH	9 INCH	9.5 INCH		12 INCH
HEIGHT (IN)	14.6	16.4	16.4		17.6
WATER CAPACITY (LBS)	15.8	26.7	29.7		49.6
DIAMETER (IN)	7.5	9	9.5		12
CYLINDER VOLUME (CU. IN)	438	739	822		1,378
<b>STANDARD SPECIFICATION</b>					
SERVICE PRESSURE (PSIG)	260	260	260		260
TEST PRESSURE (PSIG)	325	325	325		325
<b>OPTIONAL SPECIFICATION</b>					
SERVICE PRESSURE (PSIG)	400	-	400	320	320
TEST PRESSURE (PSIG)	500	-	500	400	400

All dimensions are approximate.



#### Features

- Rounded edges for safe handling
- Comfort grip for improved handling
- Arched design for light weight, enhanced durability and increased strength
- Wide 3.2" opening for easy valve access and filling

#### Stamps Of Authenticity

Guaranteed Quality. Guaranteed Worthington.





## REFRIGERANT

## DOT 39 NON-REFILLABLE



### SPECIFICATIONS

#### METRIC

MODEL	7.5 INCH	9 INCH	9.5 INCH		12 INCH
HEIGHT (MM)	369.8	416.7	416.7		446
WATER CAPACITY (KG)	7.04	11.9	13.2		22.1
DIAMETER (MM)	190.5	228.6	241.3		304.8
CYLINDER VOLUME (L)	7.2	12.1	13.5		22.5
<b>STANDARD SPECIFICATION</b>					
SERVICE PRESSURE (BAR)	17.9	17.9	17.9		17.9
TEST PRESSURE (BAR)	23	23	23		23
<b>OPTIONAL SPECIFICATION</b>					
SERVICE PRESSURE (BAR)	27.6	-	27.6	22	22
TEST PRESSURE (BAR)	35	-	35	28	28

All dimensions are approximate.



#### Features

- Rounded edges for safe handling
- Comfort grip for improved handling
- Arched design for light weight, enhanced durability and increased strength
- Wide 3.2" opening for easy valve access and filling

#### Stamps Of Authenticity

Guaranteed Quality. Guaranteed Worthington.

