

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name or designation of the mixture	Propane
Registration number	-
Synonyms	None.
SDS number	WC002
Issue date	11-April-2014
Version number	04
Revision date	21-March-2021
Supersedes date	18-February-2019

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Soldering and brazing.
Uses advised against	None known.

### 1.3. Details of the supplier of the safety data sheet

Manufacturer/Supplier	Worthington Cylinders GmbH
Address	Beim Flaschenwerk 1, A-3291 Kienberg bei Gaming Austria
E-mail	SDSRequest@worthingtonindustries.com
Telephone	1-800-359-9678
Emergency telephone	1-703-527-3887 International / CHEMTREC 1-800-424-9300 US (CCN 628056)

### 1.4. Emergency telephone number

General in EU	112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
---------------	---

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

##### Physical hazards

Flammable gases	Category 1A	H220 - Extremely flammable gas.
Gases under pressure	Liquefied gas	H280 - Contains gas under pressure; may explode if heated.

### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

##### Hazard pictograms



**Signal word** Danger

##### Hazard statements

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.

##### Precautionary statements

###### Prevention

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
------	--

###### Response

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
P381 In case of leakage, eliminate all ignition sources.

#### Storage

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

#### Disposal

Not assigned.

#### Supplemental information on the label

None.

#### 2.3. Other hazards

May displace oxygen and cause rapid suffocation. Contact with liquefied gas may cause frostbite. This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Propane	87.5 - 100	74-98-6 200-827-9	-	601-003-00-5	
		<b>Classification:</b> Flam. Gas 1A;H220, Press. Gas;H280			U
Propylene	0 - 10	115-07-1 204-062-1	-	601-011-00-9	
		<b>Classification:</b> Flam. Gas 1A;H220, Press. Gas;H280			U
Ethane	0 - 7	74-84-0 200-814-8	-	601-002-00-X	
		<b>Classification:</b> Flam. Gas 1A;H220, Press. Gas;H280			U
Butane	0 - 2.5	106-97-8 203-448-7	-	601-004-01-8	
		<b>Classification:</b> Flam. Gas 1A;H220, Press. Gas;H280			C,S,U

##### Additives

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Ethyl mercaptan	< 0.005	75-08-1 200-837-3	-	016-022-00-9	

#### List of abbreviations and symbols that may be used above

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note S: This substance may not require a label according to Article 17 (see section 1.3 of Annex I) (Table 3.1). This substance may not require a label according to Article 23 of Directive 67/548/EEC (see section 8 of Annex VI to that Directive) (Table 3.2).

Note U (Table 3.1): When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

#### Composition comments

The full text for all H-statements is displayed in section 16.  
Gas concentrations are in percent by volume.

### SECTION 4: First aid measures

##### General information

First aid personnel must be aware of own risk during rescue. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 4.1. Description of first aid measures

##### Inhalation

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory tract irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

##### Skin contact

Not likely, due to the form of the product. If frostbite occurs, immerse affected area in warm water (not exceeding 105°F/41°C). Keep immersed for 20 to 40 minutes. Get medical attention immediately.

##### Eye contact

Not likely, due to the form of the product. If frostbite occurs, immediately flush eyes with plenty of warm water (not exceeding 105°F/41°C) for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention promptly if symptoms persist or occur after washing.

##### Ingestion

This material is a gas under normal atmospheric conditions and ingestion is unlikely.

<b>4.2. Most important symptoms and effects, both acute and delayed</b>	Exposure to rapidly expanding gas or vapourizing liquid may cause frostbite ("cold burn"). Very high exposure can cause suffocation from lack of oxygen. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect himself.
<b>4.3. Indication of any immediate medical attention and special treatment needed</b>	Exposure may aggravate pre-existing respiratory disorders. Provide general supportive measures and treat symptomatically.

## SECTION 5: Firefighting measures

<b>General fire hazards</b>	Extremely flammable gas. Contents under pressure. Pressurised container may explode when exposed to heat or flame.
<b>5.1. Extinguishing media</b>	
<b>Suitable extinguishing media</b>	Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ). Water fog. Foam.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>5.2. Special hazards arising from the substance or mixture</b>	Extremely flammable gas. May form explosive mixtures with air. Gas may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
<b>5.3. Advice for firefighters</b>	
<b>Special protective equipment for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Special fire fighting procedures</b>	Do not extinguish fires unless gas flow can be stopped safely; explosive re-ignition may occur. Promptly isolate the scene by removing all persons from the vicinity of the incident. No action shall be taken involving any personal risk or without suitable training. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus. Stop flow of material. Use water to keep fire exposed containers cool and to protect personnel effecting shutoff. If a leak or spill has not ignited, use water spray to disperse the vapors and to protect personnel attempting to stop leak. Prevent runoff from fire control or dilution from entering streams, sewers or drinking water supply.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Cool containers exposed to flames with water until well after the fire is out.

## SECTION 6: Accidental release measures

<b>6.1. Personal precautions, protective equipment and emergency procedures</b>	
<b>For non-emergency personnel</b>	Evacuate the area promptly. Keep unnecessary personnel away. Wear appropriate personal protective equipment.
<b>For emergency responders</b>	No action shall be taken involving any personal risk or without suitable training. In the event of a leak evacuate all personnel until ventilation can restore oxygen concentrations to safe levels. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Wear appropriate protective equipment and clothing during clean-up.
<b>6.2. Environmental precautions</b>	Should not be released into the environment. Prevent further leakage or spillage if safe to do so.
<b>6.3. Methods and material for containment and cleaning up</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Stop leak if you can do so without risk. If possible, turn leaking containers so that gas escapes rather than liquid. Isolate area until gas has dispersed.
<b>6.4. Reference to other sections</b>	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## SECTION 7: Handling and storage

<b>7.1. Precautions for safe handling</b>	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not smoke. All equipment used when handling the product must be grounded. Do not breathe gas. Avoid prolonged exposure. Do not enter storage areas or confined spaces unless adequately ventilated. Use only outdoors or in a well-ventilated area. Oxygen concentration should not fall below 19.5 % at sea level (pO <sub>2</sub> = 135 mmHg). Mechanical ventilation or local exhaust ventilation may be required. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
<b>7.2. Conditions for safe storage, including any incompatibilities</b>	Do not store, incinerate, or heat this material above 120 degrees Fahrenheit. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Protect cylinders from damage. Stored containers should be periodically checked for general condition and leakage. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s) Soldering and brazing.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1810 mg/m <sup>3</sup>
		750 ppm
	TWA	1450 mg/m <sup>3</sup>
		600 ppm

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no effect levels (DNELs)** Not available.

**Predicted no effect concentrations (PNECs)** Not available.

**Exposure guidelines** Follow standard monitoring procedures.

### 8.2. Exposure controls

**Appropriate engineering controls** Provide adequate ventilation and minimize the risk of inhalation of gas. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

#### Individual protection measures, such as personal protective equipment

**General information** Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

**Eye/face protection** Wear approved safety glasses or goggles. Face shield is recommended. Eye protection should meet standard EN 166.

##### Skin protection

**- Hand protection** Wear suitable gloves tested to EN374. Wear cold insulating gloves.

**- Other** Wear protective clothing appropriate for the risk of exposure.

**Respiratory protection** If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. WARNING! Air-purifying respirators do not protect workers in oxygen deficient atmospheres.

**Thermal hazards** Contact with liquefied gas might cause frostbites, in some cases with tissue damage. Wear appropriate thermal protective clothing, when necessary.

**Hygiene measures** Do not eat, drink or smoke when using the product. Wash thoroughly after handling. Provide eyewash station and safety shower. Handle in accordance with good industrial hygiene and safety practices.

**Environmental exposure controls** Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Gas.
<b>Form</b>	Compressed liquefied gas.
<b>Colour</b>	Colourless.
<b>Odour</b>	Rotten egg.
<b>Odour threshold</b>	Not determined.
<b>Melting point/freezing point</b>	-188 °C (-306.4 °F)
<b>Boiling point or initial boiling point and boiling range</b>	-42 °C (-43.6 °F) 14.7 psia
<b>Flammability</b>	Extremely flammable gas.
<b>Lower and upper explosion limit</b>	
<b>Flash point</b>	-104.0 °C (-155.2 °F)

<b>Auto-ignition temperature</b>	432 °C (809.6 °F)
<b>Decomposition temperature</b>	Not determined.
<b>pH</b>	Not applicable.
<b>Kinematic viscosity</b>	Not determined.
<b>Solubility</b>	
<b>Solubility (water)</b>	Slightly soluble in water.
<b>Partition coefficient n-octanol/water (log value)</b>	1.77
<b>Vapour pressure</b>	127 psig (21°C / 70°F)
<b>Density and/or relative density</b>	
<b>Density</b>	Not determined.
<b>Relative density</b>	0.504 (liquid) 1.5 (vapour) (Air=1) (15 °C (59 °F))
<b>Vapour density</b>	Not determined.
<b>Particle characteristics</b>	
<b>Particle size</b>	Not applicable.

## 9.2. Other information

**9.2.1. Information with regard to physical hazard classes** No relevant additional information available.

### 9.2.2. Other safety characteristics

<b>Evaporation rate</b>	Not determined.
<b>Molecular weight</b>	45 g/mol
<b>Percent volatile</b>	100 %
<b>Viscosity</b>	Not applicable.

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	Reacts violently with strong oxidants, nitrites, inorganic chlorides, chlorites and perchlorates causing fire and explosion hazard.
<b>10.2. Chemical stability</b>	Stable under normal temperature conditions and recommended use.
<b>10.3. Possibility of hazardous reactions</b>	Polymerization will not occur. May form explosive mixture with air. This product may react with oxidizing agents.
<b>10.4. Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>10.5. Incompatible materials</b>	Strong oxidising agents. Halogens. Nitrates.
<b>10.6. Hazardous decomposition products</b>	Thermal decomposition of this product can generate carbon monoxide and carbon dioxide. Hydrocarbons.

## SECTION 11: Toxicological information

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

### Information on likely routes of exposure

<b>Inhalation</b>	High concentrations: Suffocation (asphyxiant) hazard - if allowed to accumulate to concentrations that reduce oxygen below safe breathing levels. Breathing of high concentrations may cause dizziness, light-headedness, headache, nausea and loss of co-ordination. Continued inhalation may result in unconsciousness.
<b>Skin contact</b>	Contact with liquefied gas may cause frostbite.
<b>Eye contact</b>	Contact with liquefied gas may cause frostbite.
<b>Ingestion</b>	This material is a gas under normal atmospheric conditions and ingestion is unlikely.

**Symptoms** Exposure to rapidly expanding gas or vapourizing liquid may cause frostbite ("cold burn"). Very high exposure can cause suffocation from lack of oxygen. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themselves.

### 11.1. Information on toxicological effects

**Acute toxicity** Not expected to be acutely toxic.

Components	Species	Test Results
Propane (CAS 74-98-6) <b>Acute</b> <b>Inhalation</b> Gas LC50	Rat	> 80000 ppm, 15 Minutes
Propylene (CAS 115-07-1) <b>Acute</b> <b>Inhalation</b> Gas LC50	Rat	> 65000 ppm, 4 Hours
<b>Skin corrosion/irritation</b>	Based on available data, the classification criteria are not met.	
<b>Serious eye damage/eye irritation</b>	Based on available data, the classification criteria are not met.	
<b>Respiratory sensitisation</b>	Based on available data, the classification criteria are not met.	
<b>Skin sensitisation</b>	Based on available data, the classification criteria are not met.	
<b>Germ cell mutagenicity</b>	Based on available data, the classification criteria are not met.	
<b>Carcinogenicity</b>	Based on available data, the classification criteria are not met.	
<b>Reproductive toxicity</b>	Based on available data, the classification criteria are not met.	
<b>Specific target organ toxicity - single exposure</b>	Based on available data, the classification criteria are not met.	
<b>Specific target organ toxicity - repeated exposure</b>	Based on available data, the classification criteria are not met.	
<b>Aspiration hazard</b>	Not relevant, due to the form of the product.	
<b>Mixture versus substance information</b>	No information available.	
<b>11.2. Information on other hazards</b>		
<b>Endocrine disrupting properties</b>	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.	
<b>Other information</b>	Exposure over a long period of time may cause central nervous system effects.	
<b>SECTION 12: Ecological information</b>		
<b>12.1. Toxicity</b>	The product is not expected to be hazardous to the environment.	
<b>12.2. Persistence and degradability</b>	Not relevant, due to the form of the product.	
<b>12.3. Bioaccumulative potential</b>	Not relevant, due to the form of the product.	
<b>Bioconcentration factor (BCF)</b>	Not available.	
<b>12.4. Mobility in soil</b>	Not relevant, due to the form of the product.	
<b>12.5. Results of PBT and vPvB assessment</b>	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.	
<b>12.6. Endocrine disrupting properties</b>	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.	
<b>12.7. Other adverse effects</b>	The product contains volatile organic compounds which have a photochemical ozone creation potential.	
<b>SECTION 13: Disposal considerations</b>		
<b>13.1. Waste treatment methods</b>		
<b>Residual waste</b>	Dispose in accordance with all applicable regulations.	
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal.	
<b>EU waste code</b>	16 05 04* The waste code should be assigned in discussion between the user, the producer and the waste disposal company. The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.	
<b>Disposal methods/information</b>	Use the container until empty. Do not dispose of any non-empty container. Empty containers have residual vapor that is flammable and explosive. Cylinders should be emptied and returned to a hazardous waste collection point. Do not puncture or incinerate even when empty. Dispose in accordance with all applicable regulations.	

**Special precautions**

Dispose of in accordance with local regulations.

**SECTION 14: Transport information****ADR**

<b>14.1. UN number</b>	UN1075
<b>14.2. UN proper shipping name</b>	PETROLEUM GASES, LIQUEFIED
<b>14.3. Transport hazard class(es)</b>	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Hazard No. (ADR)	23
Tunnel restriction code	B/D
<b>14.4. Packing group</b>	-
<b>14.5. Environmental hazards</b>	No
<b>14.6. Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**RID**

<b>14.1. UN number</b>	UN1075
<b>14.2. UN proper shipping name</b>	PETROLEUM GASES, LIQUEFIED
<b>14.3. Transport hazard class(es)</b>	
Class	2.1
Subsidiary risk	-
Label(s)	2.1 (+13)
<b>14.4. Packing group</b>	-
<b>14.5. Environmental hazards</b>	No
<b>14.6. Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**ADN**

<b>14.1. UN number</b>	UN1075
<b>14.2. UN proper shipping name</b>	PETROLEUM GASES, LIQUEFIED
<b>14.3. Transport hazard class(es)</b>	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
<b>14.4. Packing group</b>	-
<b>14.5. Environmental hazards</b>	No
<b>14.6. Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**IATA**

<b>14.1. UN number</b>	UN1075
<b>14.2. UN proper shipping name</b>	Petroleum gases, liquefied
<b>14.3. Transport hazard class(es)</b>	
Class	2.1
Subsidiary risk	-
<b>14.4. Packing group</b>	-
<b>14.5. Environmental hazards</b>	No
<b>ERG Code</b>	10L
<b>14.6. Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**IMDG**

<b>14.1. UN number</b>	UN1075
<b>14.2. UN proper shipping name</b>	PETROLEUM GASES, LIQUEFIED
<b>14.3. Transport hazard class(es)</b>	
Class	2.1
Subsidiary risk	-
<b>14.4. Packing group</b>	-
<b>14.5. Environmental hazards</b>	
Marine pollutant	No
<b>EmS</b>	E-D, S-U

**14.6. Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**14.7. Maritime transport in bulk according to IMO instruments** Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

**Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended**

Not listed.

**Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended**

Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**

Not listed.

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**

Not listed.

#### Authorisations

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended**

Not listed.

#### Restrictions on use

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**

Ethyl mercaptan (CAS 75-08-1)

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.**

Not listed.

#### Other EU regulations

**Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended**

Ethyl mercaptan (CAS 75-08-1)

#### Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

#### National regulations

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended.  
Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

#### List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG Code: International Maritime Dangerous Goods Code.

LC50: Lethal Concentration, 50%.

MARPOL: International Convention for the Prevention of Pollution from Ships.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short-Term Exposure Limit.

TWA: Time Weighted Average Value.



**References**

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices  
EPA: AQUIRE database  
HSDB® - Hazardous Substances Data Bank  
IARC Monographs. Overall Evaluation of Carcinogenicity  
National Toxicology Program (NTP) Report on Carcinogens  
NLM: Hazardous Substances Data Base

**Information on evaluation method leading to the classification of mixture**

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

**Full text of any H-statements not written out in full under Sections 2 to 15**

H220 Extremely flammable gas.  
H280 Contains gas under pressure; may explode if heated.

**Training information**

Follow training instructions when handling this material.

**Disclaimer**

All information in this Safety Data Sheet is believed to be accurate and reliable. However, no guarantee or warranty of any kind is made with regard to the accuracy of information or the suitability of the recommendations contained herein. It is the user's responsibility to assess the safety and toxicity of this product under their own conditions of use and to comply with all applicable laws and regulations.