


REFRIGERANT
REFILLABLE CYLINDERS

STANDARD SPECIFICATIONS

MODEL	30 LBS	123 LBS	239 LBS	1,000 LBS
HEIGHT (IN)	19.8	54.8	48.7	57.3
WATER CAPACITY (LBS)	30	123	239	1,000
NOMINAL TARE WEIGHT (LBS)	21	58	78.5	334
CYLINDER DIAMETER (IN)	9.1	10	14.7	30
CYLINDER VOLUME (CU. IN)	830	3,393	6,515	27,461
COLLAR DIAMETER (IN)	8	3.9	11.4	16
COLLAR HEIGHT (IN)	5.1	-	6.4	6.9
FOOTRING DIAMETER (IN)	6.9	10	14.5	22
STANDARD SPECIFICATION	DOT-4BA-400	DOT-4BW400	DOT-4BW260	DOT-4BW-260
SERVICE PRESSURE (PSIG)	400	400	260	260
TEST PRESSURE (PSIG)	800	800	520	520
OPTIONAL SPECIFICATION	-	-	DOT-4BW400	DOT-4BW-400
SERVICE PRESSURE (PSIG)	-	-	400	400
TEST PRESSURE (PSIG)	-	-	800	800

All tare weights and dimensions are approximate.
 Cylinder photos are not shown to scale.

Container Color Guidelines

Worthington complies with AHRI Guideline N, which states all refrigerant containers will be painted PMS 413. Per SAE, containers with R-134a Automotive will remain PMS 2975. Containers with flammable refrigerant will have a red band on the shoulder.



For more information, contact a Worthington Industries representative today.

200 OLD WILSON BRIDGE ROAD
 COLUMBUS, OHIO 43085
 614.438.3013

TOLL-FREE: 866.928.2657
 CYLINDERS@WORTHINGTONINDUSTRIES.COM
 WORTHINGTONINDUSTRIES.COM/REFRIGERANTS


REFRIGERANT
REFILLABLE CYLINDERS

METRIC SPECIFICATIONS

MODEL	30 LBS	123 LBS	239 LBS	1,000 LBS
HEIGHT (MM)	503	1,392	1,237	1,455
WATER CAPACITY (KG)	13.6	55.8	108.4	450
NOMINAL TARE WEIGHT (KG)	9.3	26.3	35.6	151.5
CYLINDER DIAMETER (MM)	231.1	254	373.4	762
CYLINDER VOLUME (L)	13.6	55.8	108.4	450
COLLAR DIAMETER (MM)	203.2	98.4	289.6	406.4
COLLAR HEIGHT (MM)	130	-	163	175
FOOTRING DIAMETER (MM)	175	254	368.3	558.8
STANDARD SPECIFICATION	DOT-4BA-400	DOT-4BW400	DOT-4BW260	DOT-4BW-260
SERVICE PRESSURE (BAR)	28	27	18	18
TEST PRESSURE (BAR)	55	54	36	36
OPTIONAL SPECIFICATION	-	-	DOT-4BW400	DOT-4BW-400
SERVICE PRESSURE (BAR)	-	-	27	27
TEST PRESSURE (BAR)	-	-	54	54

All tare weights and dimensions are approximate.
 Cylinder photos are not shown to scale.

Container Color Guidelines

Worthington complies with AHRI Guideline N, which states all refrigerant containers will be painted PMS 413. Per SAE, containers with R-134a Automotive will remain PMS 2975. Containers with flammable refrigerant will have a red band on the shoulder.



For more information, contact a Worthington Industries representative today.

200 OLD WILSON BRIDGE ROAD
 COLUMBUS, OHIO 43085
 614.438.3013

TOLL-FREE: 866.928.2657
 CYLINDERS@WORTHINGTONINDUSTRIES.COM
 WORTHINGTONINDUSTRIES.COM/REFRIGERANTS