

1. Identification

Product identifier BernzOmatic Carbon Steel Welding Rod

Other means of identification

SDS number WC041

Recommended use Welding steel

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer/Supplier Worthington Cylinder Corporation

Address 300 E. Breed St., Chilton, WI 53014
United States

Contact person Kurt Goomey

E-mail address kurt.goomey@worthingtonindustries.com

Telephone number 1-920-849-1740

Emergency telephone number 1-703-527-3887 International / CHEMTREC 1-800-424-9300 Domestic

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 2
Specific target organ toxicity, repeated exposure Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Suspected of causing cancer. Causes damage to organs (Respiratory system, Pancreas, Liver) through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Response Get medical advice/attention if you feel unwell.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) High concentrations of freshly formed fumes/dusts of metal oxides can produce symptoms of metal fume fever.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Iron	7439-89-6	90 - 100
Manganese	7439-96-5	< 3
Silicon	7440-21-3	< 3

Carbon	7440-44-0	< 1
Copper	7440-50-8	< 1

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Remove person from contaminated area to fresh air. Apply artificial respiration if needed. Call a physician if symptoms develop or persist.

Skin contact Flush skin with large amounts of water for 15 minutes. Get medical attention if irritation develops (or persists).

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove any contact lenses. Get medical attention if irritation develops and persists.

Ingestion Ingestion is not a likely route of exposure for these products. If swallowed call physician immediately! Do not induce vomiting unless directed by medical personnel. Rinse mouth with water if person is conscious. Never give fluids or induce vomiting if person is unconscious, having convulsions, or not breathing.

Most important symptoms/effects, acute and delayed Contact may cause irritation and redness. Dust may irritate respiratory system. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Typical metal fume fever begins four to twelve hours after sufficient exposure to freshly formed fumes. The first symptoms are a metallic taste, dryness and irritation of the throat. Cough and shortness of breath may occur along with headache, fatigue, nausea, vomiting, muscle and joint pain, fever and chills. The syndrome runs its course in 24-48 hours.

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

Unsuitable extinguishing media Do not use water or halogenated extinguishing media.

Specific hazards arising from the chemical Fire or high temperatures create: Metal oxides.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions Move containers from fire area if you can do it without risk.

General fire hazards Solid metal is not flammable; however, finely divided metallic dust or powder may form an explosive mixture with air.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Avoid inhalation of dust from the spilled material. Wear protective clothing as described in Section 8 of this SDS. Use personal protection recommended in Section 8 of the SDS. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and materials for containment and cleaning up Stop leak if you can do so without risk. Local authorities should be advised if significant spillages cannot be contained. Collect for salvage or disposal. Put material in suitable, covered, labeled containers. Avoid the generation of dusts during clean-up. For waste disposal, see Section 13 of the SDS.

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not contaminate water.

7. Handling and storage

Precautions for safe handling Follow the recommendations in ANSI Z49.1, Safety in welding and cutting (ANSI=American National Standard Institute). Avoid inhalation of dust and fumes. Use process enclosures, local exhaust ventilation, or other engineering controls to control sources of dust and fumes. Keep formation of airborne dusts to a minimum. Avoid contact with skin and eyes. Wear appropriate personal protective equipment (See Section 8). Do not eat, drink or smoke when using the product. Wash thoroughly after handling. Avoid release to the environment.

Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Store in a closed container away from incompatible materials. Keep away from food, drink and animal feedingstuffs.

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

Components	Type	Value
Carbon (CAS 7440-44-0)	TWA	15 mppcf

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Carbon (CAS 7440-44-0)	PEL	5 mg/m ³ 15 mg/m ³	Respirable fraction. Total dust.
Copper (CAS 7440-50-8)	PEL	1 mg/m ³ 0.1 mg/m ³	Dust and mist. Fume.
Manganese (CAS 7439-96-5)	Ceiling	5 mg/m ³	Fume.
Silicon (CAS 7440-21-3)	PEL	5 mg/m ³ 15 mg/m ³	Respirable fraction. Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value
Carbon (CAS 7440-44-0)	TWA	15 mppcf

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Carbon (CAS 7440-44-0)	TWA	2 mg/m ³	Respirable fraction.
Copper (CAS 7440-50-8)	TWA	1 mg/m ³ 0.2 mg/m ³	Dust and mist. Fume.
Manganese (CAS 7439-96-5)	TWA	0.1 mg/m ³ 0.02 mg/m ³	Inhalable fraction. Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Carbon (CAS 7440-44-0)	TWA	2.5 mg/m ³	Respirable.
Copper (CAS 7440-50-8)	TWA	1 mg/m ³	Dust and mist.
Manganese (CAS 7439-96-5)	STEL	3 mg/m ³	Fume.
	TWA	1 mg/m ³	Fume.
Silicon (CAS 7440-21-3)	TWA	5 mg/m ³ 10 mg/m ³	Respirable. Total

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

No exposure standards allocated.

Appropriate engineering controls

Provide adequate ventilation. Keep melting/soldering temperatures as low as possible to minimize the generation of fume. Observe occupational exposure limits and minimize the risk of inhalation of dust and fumes. Shower, hand and eye washing facilities near the workplace are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). When welding, it is recommended that safety glasses, goggles, or face-shield with filter lens of appropriate shade number (per ANSI Z49.1-1988, "Safety in Welding and Cutting") be worn.

Skin protection

Hand protection

Wear protective gloves (i.e. latex, nitrile, neoprene).

Other

When welding, wear protective clothing that protects from sparks and flame (per ANSI Z49.1-1988, "Safety in Welding and Cutting"). Heat resistant/insulated gloves and clothing are recommended when working with molten material.

Respiratory protection Use a respirator when local exhaust or ventilation is not adequate to keep exposures below the OEL. In a confined space a supplied respirator may be required. Selection and use of respiratory protective equipment should be in accordance with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. In case of inadequate ventilation or risk of inhalation of dust or fumes, use suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Solid steel wire or rods (which may be copper coated)

Physical state Solid.

Form Solid.

Color Not available.

Odor Odorless.

Odor threshold Not applicable

pH Not applicable

Melting point/freezing point < 2372 °F (< 1300 °C)

Initial boiling point and boiling range 5432 °F (3000 °C)

Flash point Not applicable

Evaporation rate Not applicable

Flammability (solid, gas) Non flammable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not applicable

Flammability limit - upper (%) Not applicable

Vapor pressure Not applicable

Vapor density Not applicable

Relative density 7.6 - 7.78

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not applicable

Decomposition temperature Not available.

Viscosity Not available.

Other information

Partition coefficient (oil/water) Not applicable

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Avoid molten metal contact with water. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Strong acids. Mineral acid. Halogenated compounds.

Hazardous decomposition products

Toxic metal oxides are emitted when heated above the melting point. Welding fumes and gases cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded, the process, procedure and electrodes used.

Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include: coatings on the metal being welded (such as paint, plating, or galvanizing), the number of welders and the volume of the worker area, the quality and amount of ventilation, the position of the welder's head with respect to the fume plume, as well as the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from cleaning and degreasing activities.)

Fumes can be reasonably expected to include: Metal oxides.

11. Toxicological information**Information on likely routes of exposure**

Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Inhalation	Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the respiratory tract. Inhalation of manganese oxide dust/fumes may cause metal fume fever. The symptoms are shivering, fever, malaise and muscular pain.
Skin contact	Hot or molten material may produce thermal burns. Dust may irritate skin.
Eye contact	Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the eyes.

Symptoms related to the physical, chemical and toxicological characteristics

Contact may cause irritation and redness. Dust may irritate respiratory system. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Heating above the melting point releases metallic oxides which may cause metal fume fever by inhalation. The symptoms are shivering, fever, malaise and muscular pain. Typical symptoms last 12 to 48 hours and are characterized by metallic taste in the mouth, dryness, and irritation of the throat, followed by weakness, muscle pain, fever, and chills.

Information on toxicological effects

Acute toxicity	When heated, the vapors/fumes given off may cause respiratory tract irritation. Acute overexposure to Copper dust/fume can cause irritation of the eyes, nose, throat, and skin and under severe fume overexposure can cause metal fume fever with flu-like symptoms such as sweet metal taste, dry throat, coughing, fever and chills, tight chest, dyspnea, headache, blurred vision, back pain, nausea, vomiting, fatigue. Symptoms usually disappear within 24 hours. Copper may cause skin and hair discoloration. Inhalation of copper dusts may change the gums and mucous lining of the mouth which is generally attributable to localized tissue effect rather than general toxicity.
-----------------------	--

Components	Species	Test Results
Carbon (CAS 7440-44-0)		
Acute		
<i>Oral</i>		
LD50	Rat	> 10000 mg/kg
Iron (CAS 7439-89-6)		
Acute		
<i>Oral</i>		
LD50	Rat	30 g/kg
Manganese (CAS 7439-96-5)		
Acute		
<i>Oral</i>		
LD50	Rat	9000 mg/kg
Silicon (CAS 7440-21-3)		
Acute		
<i>Oral</i>		
LD50	Rat	3160 mg/kg
Skin corrosion/irritation	Hot or molten material may produce thermal burns. Dust may irritate skin.	
Serious eye damage/eye irritation	Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the eyes.	
Respiratory or skin sensitization		
Respiratory sensitization	Not classified.	

Skin sensitization	Not classified.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Suspected of causing cancer.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Welding fume (CAS n/a)	2B Possibly carcinogenic to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Not listed.	
Reproductive toxicity	This product is not reported to cause reproductive effects in humans. Manganese metal may damage the reproductive system and has shown teratogenic effects in laboratory animals.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Causes damage to organs (Respiratory system, Pancreas, and Liver) through prolonged or repeated exposure by inhalation.
Aspiration hazard	Due to the physical form of the product it is not an aspiration hazard.
Chronic effects	Chronic inhalation of high concentrations of iron oxide fumes or dust may lead to benign pneumoconiosis (siderosis). Overexposure to manganese fumes may affect the brain and central nervous system, resulting in poor coordination, difficulty speaking, and arm or leg tremor. This condition can be irreversible.

12. Ecological information

Ecotoxicity Alloys in massive forms present a limited hazard for the environment.

Components	Species	Test Results
Copper (CAS 7440-50-8)		
Aquatic		
Fish	LC50 Fathead minnow (<i>Pimephales promelas</i>)	0.0184 - 0.042 mg/l, 96 hours
Iron (CAS 7439-89-6)		
Aquatic		
Fish	LC50 Channel catfish (<i>Ictalurus punctatus</i>)	> 500 mg/l, 96 hours

Persistence and degradability	The product is not biodegradable.
Bioaccumulative potential	The product contains potentially bioaccumulating substances.
Mobility in soil	Metals in massive form are not mobile in the environment.
Other adverse effects	None known.

13. Disposal considerations

Disposal instructions	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Recover and recycle, if practical. Solid metal and alloys in the form of particles may be reactive. Its hazardous characteristics, including fire and explosion, should be determined prior to disposal.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Copper (CAS 7440-50-8)	LISTED
Manganese (CAS 7439-96-5)	LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Manganese	7439-96-5	< 3

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Manganese (CAS 7439-96-5)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Copper (CAS 7440-50-8)
Manganese (CAS 7439-96-5)
Silicon (CAS 7440-21-3)

US. New Jersey Worker and Community Right-to-Know Act

Carbon (CAS 7440-44-0)
Copper (CAS 7440-50-8)
Manganese (CAS 7439-96-5)
Silicon (CAS 7440-21-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Copper (CAS 7440-50-8)
Manganese (CAS 7439-96-5)
Silicon (CAS 7440-21-3)
Welding fume (CAS n/a)

US. Rhode Island RTK

Copper (CAS 7440-50-8)
Manganese (CAS 7439-96-5)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Not listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 07-August-2014

Revision date -

Version # 01

HMIS® ratings
 Health: 1*
 Flammability: 0
 Physical hazard: 0

Disclaimer All information in this Material Safety Data Sheet is believed to be accurate and reliable. However, no guarantee or warranty of any kind is made with regard to the accuracy of information or the suitability of the recommendations contained herein. It is the user's responsibility to assess the safety and toxicity of this product under their own conditions of use and to comply with all applicable laws and regulations.